


# D4 SERIES

- Typical Loss 0.3dB
- Threaded coupling mechanism
- UL94 V-0 rated boots in various colors
- One piece corrosion resistant design
- RoHS compliant

## D4 CONNECTOR



CODE	FERRULE I.D.	BOOT TYPE	BOOT COLOR
CN-D4 D4 Crimp Style	125 SM: 125µm	1 900µm Smooth Fiber Short Boot	1 Blue
	126 SM: 126µm	3 2.0mm Standard Boot	2 Black
		8 3.0mm Standard Boot	3 Green
			4 Beige
			6 Red
			7 Yellow
			8 White

ORDER CODE example: **CN-D4 - 125 - 11**

CODE	FERRULE I.D.	BOOT TYPE	BOOT COLOR
CN-D4N D4 Crimp Free	125 SM: 125µm	7 3.0mm Smooth Boot	1 Blue
			2 Black
			6 Red
			8 White

ORDER CODE example: **CN-D4N - 125 - 11**

## D4 ADAPTER



CODE	SLEEVE
AD-D4 D4 Adapter	2 Phosphor Bronze Split

**AD-D4 - 2**

# SMA SERIES

- Typical Loss 0.3dB
- Stainless Alloy Ferrule
- UL94 V-0 rated boots in various colors
- One piece corrosion resistant design
- RoHS compliant

## SMA CONNECTOR



CODE	FERRULE I.D.	BOOT	BOOT
CN-SMA SMA with Hex Nut	127 MM: 127µm	8 3.0mm Standard Boot	1 Blue
	144 MM: 144µm		2 Black
	230 MM: 230µm		3 Green
	240 MM: 240µm		4 Beige
	245 MM: 245µm		6 Red
	250 MM: 250µm		7 Yellow
	360 MM: 360µm		8 White
	460 MM: 460µm		X Custom

ORDER CODE example: **CN-SMA - 250 - 82**

## SMA ADAPTER

CODE	SLEEVE
AD-SMA SMA Adapter	1 Sleeve

**AD-SMA - 1**