

ZIRCONIA SLEEVES

- Ultra low insertion loss.
- Superior Withdrawal Force
- RoHS compliant

SPECIFICATION	ST	SC, FC	LC, MU
Material	Zirconia		
Withdrawal Force	200gf~600gf	200gf~600gf	100gf~250gf
Insertion Loss	0.1dB Typical or better		
Durability	<0.02dB deviation after 1000 matings		
Outer Diameter	3.2 ±0.02mm	3.2 ±0.02mm	1.62 ±0.01mm
Inner Diameter	2.49mm	2.49mm	1.246mm
Length	10.1 ±0.1mm	11.4 ±0.1mm	6.8 + 0/-0.1mm

ZIRCONIA SLEEVES ADAPTERS



CODE		INNER DIAMETER		LENGTH	
S-ZR	Zirconia Sleeve	250	2.49mm	ST	10.1mm ST
				SC	11.4mm SC & FC

ORDER CODE example:

S-ZR - ST

CODE		INNER DIAMETER		LENGTH	
S-ZR	Zirconia Sleeve	125	1.25mm	LC	6.8mm

ORDER CODE example:

S-ZR - LC


- Ultra low insertion loss.
- Superior Withdrawal Force

PB SLEEVES

SPECIFICATION	ST	SC,FC	LC
Material	Phosphor Bronze		
Withdrawal Force	200gf~600gf		
Insertion Loss	Typical 0.1dB or better		
Outer Diameter	(3.08)mm	(3.08)mm	(1.62)mm
Inner Diameter	(2.48)mm	(2.48)mm	(1.25)mm
Length	10.1 ±0.1mm	11.4 ±0.1mm	6.8 ±0.1mm

PHOSPHOR BRONZE ADAPTER SLEEVE

CODE		INNER DIAMETER		LENGTH	
S-PB	Phosphor Bronze	250	2.48mm	ST	10.1mm ST
				SC	11.4mm SC & FC



ORDER CODE example:

S-PB - SC

CODE		INNER DIAMETER		LENGTH	
S-PB	Phosphor Bronze	200	1.98mm	104	10.4mm
				988	9.88mm

ORDER CODE example:

S-PB - 988

SLEEVE CODE		INNER DIAMETER		LENGTH	
S-PB	Phosphor Bronze	125	1.25mm	LC	6.80mm

ORDER CODE example:

S-PB - LC

Specifications may change without notice. Display Product Photos Shown are samples for viewing, not actual products. Colours and styles may vary.

www.fiberon.com